

Technical data sheet

ASPUR air purifier, Stand 19.01.2023



air 1000/2000

	air 1000TS	air1000TE	air2000TS	air2000TE	air4000TS	air4000TE
Item number	9100127S	9100126E	9100125TS	9100124TE	9100123TS	9100122TE
Power consumption (W) max.	150	150	500	500	1300	1300
Voltage (V) / frequency (Hz)	230/50	230/50	230/50	230/50	230/50	230/50
Flow rate (m ³ /h) max.	1400	1400	2400	2400	3600	3600
Flow rate (m ³ /h) range	100-1000	100-1000	200-1500	200-1500	200-2800	200-2800
Negative pressure (PA) max.	800	800	800	800	900	900
Roomsize (m ²) (at 6 times air exchange rate)	10-60	10-60	20-100	20-100	20-180	20-180
Sound pressure level (ISO 11203 at 3m distance)	20-38	20-38	20-40	20-40	30-52	30-52
Roomsize (m ²) max. (at 6 times air exchange rate)	90	90	150	150	220	220
Sound pressure level max. (ISO 11203 at 3m distance)	50	50	48	48	54	54
Filtersystem 5-stages/H14	ja	ja	ja	ja	ja	ja
Weight (kg)	95	96	100	101	125	126
Dimensions lwxhxh (mm)	500x520x1800		500x520x1800		630x650x1800	