

Technical data sheet

ASPUR air purifier, Stand 19.01.2023



air 4000

| | air 1000TS | air1000TE | air2000TS | air2000TE | air4000TS | air4000TE |
|---|-------------------|------------------|------------------|------------------|------------------|------------------|
| Item number | 9100127S | 9100126E | 9100125TS | 9100124TE | 9100123TS | 9100122TE |
| Power consumption (W) max. | 150 | 150 | 500 | 500 | 1300 | 1300 |
| Voltage (V) / frequency (Hz) | 230/50 | 230/50 | 230/50 | 230/50 | 230/50 | 230/50 |
| Flow rate (m ³ /h) max. | 1400 | 1400 | 2400 | 2400 | 3600 | 3600 |
| Flow rate (m ³ /h) range | 100-1000 | 100-1000 | 200-1500 | 200-1500 | 200-2800 | 200-2800 |
| Negative pressure (PA) max. | 800 | 800 | 800 | 800 | 900 | 900 |
| Roomsize (m ²) (at 6 times air exchange rate) | 10-60 | 10-60 | 20-100 | 20-100 | 20-180 | 20-180 |
| Sound pressure level (ISO 11203 at 3m distance) | 20-38 | 20-38 | 20-40 | 20-40 | 30-52 | 30-52 |
| Roomsize (m ²) max. (at 6 times air exchange rate) | 90 | 90 | 150 | 150 | 220 | 220 |
| Sound pressure level max. (ISO 11203 at 3m distance) | 50 | 50 | 48 | 48 | 54 | 54 |
| Filtersystem 5-stages/H14 | ja | ja | ja | ja | ja | ja |
| Weight (kg) | 95 | 96 | 100 | 101 | 125 | 126 |
| Dimensions lwxh (mm) | 500x520x1800 | | 500x520x1800 | | 630x650x1800 | |